
Product data sheet

RING 50
RG50Z-109272-LXXXM
LUX-IT




pendant mounted dir-indir LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	5.88 W	CRI	90
Total flux	596 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	5.88 W

Mounting mode

Pendant

Shape and measurements

Length: 41.34 in
Width: 41.34 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 47.04 W

Protection

IP: 20
Designation labels: CE