


Product data sheet


BARIS 40 LED UGR PLUS Z 2400LM I KL. IP20 1140MM 840 19W ANODA CO 60D
769504

LENA LIGHTING



769504 BARIS 40 LED UGR PLUS Z 2400lm I kl. IP20 1140mm 840 19W Anoda CO 60D The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2400 lm	LOR	100%
Luminous efficacy	126 lm/W	Total power	19 W

Mounting mode

Pendant

Shape and measurements

Length: 44.88 in

Width: 1.57 in

Height: 2.09 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: Silver gray

Electric

System power: 19 W

Appliance Class: I

Protection

IP: 20

IK: 03

Designation labels: CE