


Product data sheet

LUGTRACK EVO LED 1435 4200LM 4000K ROTATIONALLY-SYMMETRIC WHITE
080151.3L02.12
LUG



Modern LED luminaire for quick assembly; the construction of the luminaire enables quick and easy connection into long lighting systems, with easily interchangeable lighting modules. Mounting: suspended, surface mounted Body: coated steel sheet Power: 220-240V 50/60Hz Lifetime (L80B10): 100 000 h Additional information: support rail made of sheet metal coated in RAL 9003 mat; available with 5- and 7-pole through wiring; grill Other remarks: to power each light string, a STARTER KIT needs to be ordered; depending on the type of assembly, select and order the appropriate mounting bracket (accessories) Warranty: 5 years Application: supermarkets, warehouses, logistics centers, warehouses, production halls, pathways Type of optics: diffuser - microprismatic plexiglass (MPRM)

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	33 W	CRI	80
Total flux	4200 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	33 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 56.50 in
Width: 2.95 in
Height: 1.30 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 33 W
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 04