Product data sheet

POZZO SCALE OPAL PENDANT DIR D500 830 OR CLO
56116-533
FAGERHULT




FAGERHULT

IP 20

Installation Top point suspension in ceiling cup, c/c 48 mm. Height adjustment is made via friction lock. The ceiling cup can be mounted on sloping ceilings with a gradient of up to 20 degrees. Connection For connection with 230v built-in LED driver. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. 1-phase through-wiring possible. Surface mounted mains cable possible 180°. The luminaire is equipped with 2.6 m (Ø 500, Ø 650) or 3.8 m (Ø 850) cable, 5 x 0.75 mm², between luminaire and ceiling cup. Design Metal housing with white (RAL 9016) structured finish. Louvre Opal – plate in opal acrylic (PMMA). Delta – microprism louvre in acrylic (PMMA.). Light Distribution Direct/indirect 65/35. Dimming DALI/Phase-pulse control as standard. Miscellaneous A cut-out in the ceiling cup is made using cutters 94248 for a surface mounted mains cable.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	2256 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	19 W

Mounting mode

Pendant

Shape and measurements

Length: 19.88 in
Width: 19.88 in
Height: 2.06 in

Adjustability

Height adjustable

Design

Color of housing: White

Electric

System power: 19 W

Protection

IP: 20