


Product data sheet

ICON 24 LED HELDER F3T3
4480X2XX
PROLUMIA




Light Source: Philips LumiLEDs Luxeon TX Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 75 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours LED driver (included): Meanwell / Philips Xitanium Input: 220-240V AC 50/60Hz Power factor: > 0,95


Light output 1




1 x LED			
Nominal lamp power	12 W	LOR	100%
Lamp flux	1200 lm	Total flux	1200 lm
Luminous efficacy	100 lm/W	Total power	12 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	31 W	LOR	100%
Lamp flux	2800 lm	Total flux	2800 lm
Luminous efficacy	90 lm/W	Total power	31 W
CCT	4000 K		
CRI	80		




1 x LED			
Nominal lamp power	26 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	92 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	31 W
Lamp flux	2800 lm
Luminous efficacy	90 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	2800 lm
Total power	31 W



1 x LED

Nominal lamp power	26 W
Lamp flux	2400 lm
Luminous efficacy	92 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	2400 lm
Total power	26 W



1 x LED

Nominal lamp power	19 W
Lamp flux	1800 lm
Luminous efficacy	95 lm/W
CCT	4000 K
CRI	80


LOR	100%
Total flux	1800 lm
Total power	19 W



1 x LED

Nominal lamp power	19 W
Lamp flux	1800 lm
Luminous efficacy	95 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	1800 lm
Total power	19 W




1 x LED

Nominal lamp power	16 W
Lamp flux	1600 lm
Luminous efficacy	100 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	1600 lm
Total power	16 W



1 x LED			
Nominal lamp power	12 W	LOR	100%
Lamp flux	1200 lm	Total flux	1200 lm
Luminous efficacy	100 lm/W	Total power	12 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1600 lm	Total flux	1600 lm
Luminous efficacy	100 lm/W	Total power	16 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Height: 10.83 in
Diameter: 22.48 in

Electric

System power: 12-31 W
Appliance Class: 0

Protection

IP: 66
IK: 08
Designation labels: CE