


Product data sheet

KOMBIC 150 SF 3200 IP43 927 OP DA WH/BK
K21SF30400P927DWB
LAMP



Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring DALI included. Insolation Class I. Lifetime: >100.000 L85 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED			
Nominal lamp power	27.5 W	LOR	100%
Lamp flux	2448 lm	Total flux	2445 lm
Luminous efficacy	89 lm/W	Total power	27.5 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.09 in
Diameter: 5.91 in

Adjustability

Fixed

Electric

System power: 27.5 W
Appliance Class: I

Protection

IP: 40