


Product data sheet

WALL MOUNTED LUMINAIRE OSLO 650-2 - WITH LOUVERS 1800K
10.12430.0VXXX + 10.42400.0V001
HESS




Round luminaire canopy, horizontally split in two, made of aluminium, plain coloured. Support elements made of aluminium, painted.
Cylindrical luminaire enclosure made of PMMA. Round luminaire body made of aluminium, optionally with or without louvers. 10.42400.0V001
PARALLEL ROHRE Wall bracket OSLO 650/650-2 Made of galvanised steel Overhanging 500 mm Colour: DB 703 or all RAL- (classic- single shades), Hess-DB and Hess-Glimmer-colours. RAL pearl-mica-metallic-shades on request.


Light output 1




1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1333 lm	ULOR	100%
Luminous efficacy	67 lm/W	Total flux	1333 lm
CCT	1800 K	Total power	20 W
CRI	40		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	1864 lm	ULOR	100%
Luminous efficacy	67 lm/W	Total flux	1864 lm
CCT	1800 K	Total power	28 W
CRI	40		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	1764 lm	ULOR	100%
Luminous efficacy	63 lm/W	Total flux	1764 lm
CCT	1800 K	Total power	28 W
CRI	40		




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

28 W
2037 lm
73 lm/W
1800 K
80

LOR
ULOR
Total flux
Total power

100%
100%
2037 lm
28 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

28 W
1772 lm
63 lm/W
1800 K
40

LOR
ULOR
Total flux
Total power

100%
100%
1772 lm
28 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
1401 lm
70 lm/W
1800 K
40

LOR
ULOR
Total flux
Total power

100%
100%
1401 lm
20 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
1461 lm
73 lm/W
1800 K
80

LOR
ULOR
Total flux
Total power

100%
100%
1461 lm
20 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
980 lm
65 lm/W
1800 K
40

LOR
ULOR
Total flux
Total power

100%
100%
980 lm
15 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
928 lm
62 lm/W
1800 K
40

LOR
ULOR
Total flux
Total power

100%
100%
928 lm
15 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
1099 lm
73 lm/W
1800 K
80

LOR
ULOR
Total flux
Total power

100%
100%
1099 lm
15 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
934 lm
62 lm/W
1800 K
40

LOR
ULOR
Total flux
Total power

100%
100%
934 lm
15 W

**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
1326 lm
66 lm/W
1800 K
40

LOR
ULOR
Total flux
Total power

100%
100%
1326 lm
20 W

Mounting mode

Wall mounted

Shape and measurements

Length: 32.48 in

Width: 25.59 in

Height: 32.76 in

Adjustability

Fixed

Electric

System power: 15-28 W

Protection

IP: 65