
Product data sheet

MULTILUME SLIM DELTA HB 600X600 4000K DALI ENSTO CLO
23202-520
FAGERHULT




FAGERHULT

IP 44

Installation Recessed mounting in ventilated or unventilated suspended ceilings. Two optional designs. VTB – for suspended ceilings with visible T-bars 15 or 24 mm. HB – for suspended ceiling with concealed T-bars/D-edge, symmetrical attachment of ceiling boards. Connection Connection in separate ballast box. The driver box can be positioned next to the luminaire. Snap-in terminal block 3x1,5mm2 (x2), through-wiring possible. 5x1,5mm2 (x2) when dimming. Can also be supplied with earthed mains cable and plug. Design Luminaire body of white enamelled sheet steel (RAL 9016). Louvre Delta – microprism louvre in UV stabil polystyrene. Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27 W	CRI	80
Total flux	3693 lm	LOR	100%
Luminous efficacy	137 lm/W	Total power	27 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.58 in
Width: 23.58 in
Height: 0.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 27 W

Protection

IP: 44