Product data sheet


CAPSULE 1 SURFACE FACADE LUMINAIRES
CA-30306-O-8027
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour TW (2700K - 6500K) - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Two cable entries for through wiring - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Opal, impact-resistant, UV-stabilised, polycarbonate diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	16 W	CRI	80
Total flux	1131 lm	LOR	100%
Luminous efficacy	71 lm/W	ULOR	100%
		Total power	16 W

Mounting mode

Wall mounted

Shape and measurements

Length: 7.48 in
Width: 13.39 in
Height: 4.92 in
Weight: 2.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 16 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C