

Product data sheet


LENA I (SINGLE ARM, CLEAR FROSTED GLAZING)
9.786.1052.06
LEIPZIGER LEUCHTEN



IP
55

Lena I - Post luminaire designed to illuminate squares or streets. Recommended mounting heights between 4.00 m and 5,00 m for medium lighting requirements -Luminaire head made of premium aluminium with a underside finish in a special reflective white paint for maximum light reflection -Excellent street lighting properties provided by computer- optimised reflector system. Reflector made of highest grade aluminium, polished and anodised. Lamps: horizontal mounting -Luminaire glazing made of UV-stabilised impact resistant clear or clear frosted polycarbonate bowl. PMMA Resist available on request -Gear tray made in aluminium, powder coated in white -Simple wiring via a terminal -Including decorative stainless steel bracket -Luminaire head and bracket powder coated in any RAL or DB colour -Please order column with shaft \varnothing 76 mm with 6 threads M8 AZ ... 76/6M8 (full range of columns see page 428 ff) separately

Light output 1



| | | | |
|-----------------------|----------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 100 W | LOR | 85% |
| Lamp flux | 10000 lm | ULOR | 5% |
| Luminous efficacy | 74 lm/W | Total flux | 8474 lm |
| CCT | 3000 K | Total power | 115 W |
| CRI | 90 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 14.17 in

Diameter: 26.38 in

Adjustability

Height adjustable

Electric

System power: 115 W

Protection

IP: 55