



Product data sheet

FLEX50
FX50H-R29302-LXXXM
EGLO




pendant mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2.26 W	CRI	90
Total flux	248 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	71%
		Total power	2.26 W

Mounting mode

Pendant

Shape and measurements

Length: 24.02 in

Width: 25.12 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 18.08 W

Protection

IP: 20

Designation labels: CE