

# Product data sheet


ELLK92 LED 800A 2/6 M25K V-CG-S 5700K  
12266516103  
EATON EMERGENCY LIGHTING



IP  
66


• >20 % energy savings compared to similar fluorescent luminaires • Special LED design with direct light distribution • Proved technology. The EVG 09 has been used as a driver for more than 20 years • Various light colour temperatures available - 4000 K / 5700 K • Selected LED chips with perfect binning, low power loss and long life • Ex-e technology for easy maintenance • For ambient temperatures from -25 °C up to +55 °C

## Light output 1 (integrated, emergency)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 5700 K |
| Nominal lamp power | 29 W    | CRI         | 80     |
| Total flux         | 2675 lm | LOR         | 100%   |
| Luminous efficacy  | 92 lm/W | ULOR        | 4%     |
|                    |         | Total power | 29 W   |

## Light output 2 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 5700 K |
| Nominal lamp power | 29 W     | CRI         | 80     |
| Total flux         | 5350 lm  | LOR         | 100%   |
| Luminous efficacy  | 184 lm/W | ULOR        | 4%     |
|                    |          | Total power | 29 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 53.54 in

Width: 7.40 in

Height: 5.12 in

## Adjustability

Fixed

## Electric

System power: 58 W

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 66