Product data sheet

SRT-SYSTEM IP64-SRGSVCT XP/1500 LED - GERÄTETRÄGER VARIABEL CENTRAL.LINE.OPTIC | DEVICE MOUNT VARIABL… 4000 840 IP64 DALI2 VW RAL 9016 (SRT+19527016000)


REGIOLUX



IP 64 IK 03 CE

SRT-Quick-fit mounting system, IP 64 variable device mount, Modullänge/1500. Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Variable position on the support rail. Housing colour traffic white RAL 9016. Performance level: Xtreme Performance (XP) - For the most demanding tasks, the best possible performance, durability and warranty period at the highest level, Light distribution direct, narrow distribution by means of Central.Line.Optic of PMMA plastic, the lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge to form a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1535mm x 55mm x 37mm Beam angle: 25°(C0)/80° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG0 LED service life: 100000h L90/B10 (Tq 50°C), 100000h L90/B50 (Tq 50°C) Nominal luminous flux: 4402lm Luminaire luminous efficiency: 213lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 21W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 50°C) Ambient temperatur: ta -20°C to 50°C Special properties: Ready for IoT UGR lat./long.: max. 15.8 / 20.8 Certification mark: IP64, Protection class I, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 10 years (ta -20°C to 50°C) Regiolux GmbH Type: SRGSVCT XP /1500 LED 4000 840 DALI2 vw RAL 9016 Article number: 19527016000 Product deep link: https://www.regiolux.de/en/article/19527016000 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	20.7 W	CRI	80
Total flux	4402 lm	LOR	100%
Luminous efficacy	213 lm/W	Total power	20.7 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 20.7 W
Appliance Class: 0

Design

Color of housing: White

Protection

IP: 64

IK: 03

Designation labels: CE, ENEC