



Product data sheet

PLANOS IP54
925384.002.76
RZB



Series: Planos Type of Protection: IP 54 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz LED-Lichtbandeinsatz für Tragschiene. LED-Abdeckung durch Kunststoffpanel (PMMA) mit integriertem dreireihigen Linsensystem. Lichtverteilung engstrahlend. Die Phaseneinstellung (L1, L2, L3) ist am Lichtbandeinsatz frei einstellbar. Mit 5-poliger Anschlussklemme. LED-Konverter sind für Notbeleuchtungen gemäß IEC 60598-2-22 geeignet. Available Colours: white Type of Installation: modular elements Dimensions: L 1500, B 70, H 51 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Operating Mode Lamp 1: Converter, dimmable, DALI Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 5050lm System power: 29W Beam Angle: 91°/92° Unified Glare Ratio: 19,4 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	144 lm/W	Total power	35 W

Mounting mode

Wall mounted

Electric

System power: 35 W

Shape and measurements

Length: 2.76 in
Width: 60.24 in
Height: 2.36 in

Protection

IP: 54
IK: 03

Adjustability

Fixed