Product data sheet


LIGHTSTREAM MIDI
721720.1131.1
RZB



IP 65 IK 05

Series: LIGHTSTREAM midi LED floodlight for accent and area lighting. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Bracket: aluminium, powder-coated. Tilt angle can be adjusted with angular scale. With membrane valve as a standard to avoid condensed water. Asymmetrical area flood reflector of MIRO-SILVER with reflex-boosted coating. Toughened glass cover. COB LED with socket for easy replacement. Asymmetrical light distribution. Quick connection possible without opening the housing by screw-less plug connector on bayonet locked slide. Piano-key terminal up to 5 x 2,5 mm², max cable Ø 13 mm. Windage area Aw = 0,036 m². Colour: anthracite metallic (DB703) Length: 382 mm Width: 330 mm Height: 215 mm Lamp: LED System power: 114 W Rated luminous flux: 12400 lm Luminous efficiency: 109 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	114 W	CRI	80
Total flux	12400 lm	LOR	28%
Luminous efficacy	109 lm/W	ULOR	8%
		Total power	114 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 12.99 in
Width: 15.04 in
Height: 8.46 in

Adjustability

Tiltable

Electric

System power: 114 W

Protection

IP: 65
IK: 05