

Product data sheet

FLAT POLYMERO

311923.002.4

RZB




IP
40

IK
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic (polycarbonate). Diffuser fastening: push lock. Available Colours: white Type of Installation: Pendant Dimensions: D 620, H 160 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 3200lm System power: 28W Beam Angle: 117° Number of fittings B10A: 15 Number of fittings B16A: 25 Number of fittings C10A: 26 Number of fittings C16A: 42 Inrush current: 10A Unified Glare Ratio: 18,9 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	3200 lm	LOR	100%
Luminous efficacy	114 lm/W	ULOR	8%
		Total power	28 W

Mounting mode

Pendant

Electric

System power: 28 W

Shape and measurements

Height: 6.30 in

Diameter: 24.41 in

Protection

IP: 40

IK: 10

Adjustability

Fixed