

# Product data sheet

FLAT POLYMERO  
311946.002.3.191  
RZB




IP  
40

IK  
03

Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Slave luminaire. Can only be operated in combination with corresponding master luminaire. Colour: white Diameter: 360&#160;mm Height: 100&#160;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 83 System power: 19&#160;W Rated luminous flux: 2100&#160;lm Luminous efficiency: 111&#160;lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP&#160;40

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2100 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	11%
		Total power	19 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.94 in  
Diameter: 14.17 in

## Adjustability

Fixed

## Electric

System power: 19 W

## Protection

IP: 40  
IK: 03