
Product data sheet

3329 VISCONTI 2.0 - LARGE AREAS 3000K CRI 70 68W CLD GRAPHITE
328291-39
DISANO



Housing: in die-cast aluminium. With coupling for bracket application. Attachment: in die-cast aluminium. Optics: in high-performance PMMA resistent to high temperatures and UV rays. Diffuser: tempered glass, 5 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - waterproof connector for quick installation with no need to open the fixture. - anti-condensation valve. - temperature controller with auto-reset. - EN 61547 compliant surge protection. - CLD PROG built-in functions.

Light output 1



1 x LED

Nominal lamp power	68 W	LOR	100%
Lamp flux	9709 lm	Total flux	9708 lm
Luminous efficacy	143 lm/W	Total power	68 W
CCT	3000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 20.55 in
Width: 20.55 in
Height: 3.43 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

Electric

System power: 68 W
Appliance Class: II

Protection

IP: 66
IK: 09
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -22...122°F