


Product data sheet

ABERDEEN 1 POST TOP LUMINAIRES
ABA-20002-LC-T3-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear, acrylic PMMA diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	60.7 W	CRI	80
Total flux	7746 lm	LOR	100%
Luminous efficacy	128 lm/W	ULOR	2%
		Total power	60.7 W

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Height: 24.61 in
Diameter: 27.56 in
Weight: 16.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 60.7 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C