


Product data sheet

SUP2 M 1/LED550-940 WFL LDO WH
42927632
ZUMTOBEL



LED spotlight module with one LED spotlight unit, "midi" construction size; equipped with lens system for high quality accent lighting in museums and exhibitions spaces; combination of LED PCBs, lens and film creates uniform light distribution with high intensity and soft transitions, without stray light from the light cone; Luminaire with low voltage adapter for Zumtobel SUPERSYSTEM II (48 V) low voltage track; adapter is fixed without tools and contains electronics converting the constant voltage (48V) to constant current; lamp(s): 1/8.2W, Colour rendering Ra > 90, colour temperature 4000 K; Luminaire with WIDE FLOOD light distribution; colour tolerance: SDCM 2 initial, LED PCBs premium-selected; Luminaire luminous flux: 562 lm, Luminaire efficacy: 69 lm/W; service life: 50000h for luminous flux at 90% of initial value; dimming of illuminance, Slave luminaire for DALI control (DALI only); lamp unit can rotate through 360° and tilt through 90°; lamp unit of die-cast aluminium, coated white; optic consists of glass lens and film of plastic; front ring is for glare reduction and accommodating films; total power: 8.2 W; dimensions: 166x45x94 mm; weight: 0.19 kg; Note: Film can be replaced to achieve other light distribution patterns; ring louvre or the extended anti-glare cylinder can be exchanged for the front ring.

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 8.2 W | CRI | 90 |
| Total flux | 562 lm | LOR | 100% |
| Luminous efficacy | 69 lm/W | Total power | 8.2 W |

Mounting mode

Pendant

Shape and measurements

Length: 6.54 in
Width: 1.77 in
Height: 3.70 in
Weight: 0.194 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 8.2 W
Voltage: 48 V DC
Controller: DALI
Appliance Class: III

Protection

IP: 20
Designation labels: CE, ENEC