




# Product data sheet

PANEL VALUE 1200X600 TPB 65 W 4000 K WT  
4058075384361  
LEDVANCE



Rectangular recessed panel luminaires with TP(B) rated diffuser, 1200 x 600 mm. Product features: Lifetime (L70/B50): 50,000 h (at 25 °C). Extruded aluminum frame. Polystyrene diffuser (TP(B) rated). Product benefits: Value for money luminaire. 3 years guarantee. Low flicker light thanks to special electronic control gear. External driver for extended flexibility and easy installation. Emergency lighting possible with LEDVANCE Emergency Conversion Box. Areas of application: Direct replacement for luminaires with fluorescent lamps. Offices, conference rooms. Reception areas, foyers, corridors, elevators. Suitable for recessed ceiling systems with grid size of 1200 x 600 mm. Equipment / Accessories: Accessories for several mounting options available. External control gear included.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6500 W	CRI	80
Total flux	5850 lm	LOR	100%
Luminous efficacy	1 lm/W	Total power	6500 W

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 4,704.72 in  
Width: 2,342.52 in  
Height: 133.86 in  
Weight: 3600 kg

## Adjustability

Fixed

## Design

Material impression: Aluminum  
Color of housing: White

## Electric

System power: 6500 W  
Appliance Class: II

## Protection

IP: 40  
IK: 02  
Designation labels: CE

## Other operating numbers

Ambient temperature range: 14...113°F