


Product data sheet

LINEDO_4,5M_AS_11001100
9545AS.852.400.503
RZB




IP
54

IK
03


LINEDO, 104 W, 15700 lm, 850, white, on/off Continuous line luminaire, L 4547 B 58 H 76

Light output 1 (integrated)




Lamp type	LED	CCT	5000 K
Nominal lamp power	26 W	CRI	80
Total flux	3925 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	26 W

Light output 2 (integrated)




Lamp type	LED	CCT	5000 K
Nominal lamp power	26 W	CRI	80
Total flux	3925 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	26 W

Light output 3 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	26 W	CRI	80
Total flux	3925 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	26 W

Light output 4 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	26 W	CRI	80
Total flux	3925 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	26 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 179.02 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 104 W

Protection

IP: 54
IK: 03