


Product data sheet


LIGHTING PAD R 900
556-647
NIMBUS



IP
20


Extremely effective sound-absorbing acoustic luminaire, 3 cable holders on top, tool-free adjustable, embossed front fleece, colour grey dawn, diameter 910 mm, additional MH-foam on the reverse for increased sound absorption (sound absorption class A), 12 Bartenbach lenses integrated in the front fleece, 100 % direct beam, narrow beam, CRI > 90, including converter and operating device, dimmable via DALI/switchDim, the dimming unit is capable for video conferencing, please order suspension set with supply cord separately according to your individual mounting situation (length 2 m: 555-713, length 4 m: 555-714). Front fleece available in further colours: far mountain, nightfall, soft moss, vineyard, white, yellow field, black ink.

Light output 1




1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Light output 2




1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Light output 3




1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Light output 4




1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Light output 5




1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Light output 6



1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Light output 7



1 x LED


Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

3.18 W
222 lm
70 lm/W
4000 K
92

LOR
Total flux
Total power

100%
222 lm
3.18 W

Light output 8



1 x LED


Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

3.18 W
222 lm
70 lm/W
4000 K
92

LOR
Total flux
Total power

100%
222 lm
3.18 W

Light output 9



1 x LED


Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

3.18 W
222 lm
70 lm/W
4000 K
92

LOR
Total flux
Total power

100%
222 lm
3.18 W

Light output 10



1 x LED


Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

3.18 W
222 lm
70 lm/W
4000 K
92

LOR
Total flux
Total power


100%
222 lm
3.18 W

Light output 11



1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Light output 12



1 x LED			
Nominal lamp power	3.18 W	LOR	100%
Lamp flux	222 lm	Total flux	222 lm
Luminous efficacy	70 lm/W	Total power	3.18 W
CCT	4000 K		
CRI	92		

Mounting mode

Pendant

Shape and measurements

Length: 0.04 in

Width: 0.04 in

Height: 0.04 in

Adjustability

Fixed

Design

Color of housing: Yellow, Red, Blue, White, Green, Anthracite / graphite

Electric

System power: 38.16 W

Protection

IP: 20