



Product data sheet

INFINITE PRO 854MM SURFACE OPTICELL
AK11-12X8CLOS60
LEDSC4



LedsC4 Infinite Pro 854mm Surface Opticell AK11-12X8CLOS60 Lineal lighting system for indoor use. For downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opticell. Warranty: 5 Years. Product net weight (Kg): 1.89 Product length (mm): 854 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP40. LED. No. of lampholders or LEDs: 1. LED brand: TRIDONIC. Driver brand: PHILIPS. Maximum power of light source: 10.6W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 15.8. Photobiological risk: RG1. % de Flickering: <4%. Real flux (lm): 1994. Real lm/W: 169. Voltage / frequency range: 220-240V/50-60Hz. Voltage: 120. Equipment included: Yes. Total power: 11.8. Power factor: 0.95. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED			
Nominal lamp power	11.87 W	LOR	100%
Lamp flux	1994 lm	Total flux	1994 lm
Luminous efficacy	168 lm/W	Total power	11.87 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 33.46 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 11.87 W
Appliance Class: I

Protection

IP: 40