Product data sheet

LINEDO_1,2M_OH_TW
9512OH.802.476.010
RZB



IP 54 IK 04

LINEDO, 46 W, 5050 lm, 827-865, white, DALI Continuous line luminaire, L 1163 B 58 H 91

Light output 1



1 x LED

Nominal lamp power	23 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	104 lm/W	Total power	23 W
CCT	6500 K		
CRI	80		



1 x LED

Nominal lamp power	22 W	LOR	100%
Lamp flux	2525 lm	Total flux	2525 lm
Luminous efficacy	115 lm/W	Total power	22 W
CCT	4600 K		
CRI	80		



1 x LED

Nominal lamp power	23 W	LOR	100%
Lamp flux	2250 lm	Total flux	2250 lm
Luminous efficacy	98 lm/W	Total power	23 W
CCT	2700 K		
CRI	80		

Light output 2



1 x LED

Nominal lamp power	23 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	104 lm/W	Total power	23 W
CCT	6500 K		
CRI	80		



1 x LED

Nominal lamp power	22 W	LOR	100%
Lamp flux	2525 lm	Total flux	2525 lm
Luminous efficacy	115 lm/W	Total power	22 W
CCT	4600 K		
CRI	80		



1 x LED

Nominal lamp power	23 W	LOR	100%
Lamp flux	2250 lm	Total flux	2250 lm
Luminous efficacy	98 lm/W	Total power	23 W
CCT	2700 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 45.79 in
Height: 3.58 in

Adjustability

Fixed

Electric

System power: 44-46 W

Protection

IP: 54
IK: 04