
Product data sheet

KOMBIC 150 SF 2500 IP43 WB4 OP MA/BK
K21SF2540OPWB4NMB
LAMP



Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI95. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 86.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	27.4 W	LOR	100%
Lamp flux	2075 lm	Total flux	2073 lm
Luminous efficacy	76 lm/W	Total power	27.4 W
CCT	4000 K		
CRI	98		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.09 in
Diameter: 5.91 in

Adjustability

Fixed

Electric

System power: 27.4 W
Appliance Class: I

Protection

IP: 40