


Product data sheet

DOWNLIGHT 14W, 185MM
400024XX
PROLUMIA




Light source: 14Watt LED Beam angle: 65° Color rendering index: Ra>80 Operating temperature: -10°C - +50°C Rated life hours: 50.000 LED driver(included): CE LED-current: 350mA Input: 220-240Vac, 50/60Hz Power Factor: 0.80

Light output 1



1 x LED

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 14 W | LOR | 100% |
| Lamp flux | 1373 lm | Total flux | 1373 lm |
| Luminous efficacy | 98 lm/W | Total power | 14 W |
| CCT | 4000 K | | |
| CRI | 80 | | |



1 x LED

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 14 W | LOR | 100% |
| Lamp flux | 1343 lm | Total flux | 1343 lm |
| Luminous efficacy | 96 lm/W | Total power | 14 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.04 in

Diameter: 7.28 in

Electric

System power: 14 W

Appliance Class: I

Protection

IP: 20

Designation labels: CE