



# Product data sheet

KOMBIC 150 RD 2400 IP23 930 RF WF DA B/B  
K21RD2023RW930DBB  
LAMP



Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in black finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 100.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution and low UGR<19.

## Light output 1



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 19.5 W   | LOR         | 100%    |
| Lamp flux          | 2104 lm  | Total flux  | 2102 lm |
| Luminous efficacy  | 108 lm/W | Total power | 19.5 W  |
| CCT                | 3000 K   |             |         |
| CRI                | 90       |             |         |

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 3.94 in  
Diameter: 5.91 in

## Adjustability

Fixed

## Electric

System power: 19.5 W  
Appliance Class: II

## Protection

IP: 40