

Product data sheet

FLAT POLYMERO ALU

311647.002.8

RZB



IP
43

IK
10

Series: Flat Polymero Alu Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: bayonet lock. Diffuser: opal polycarbonate plastic. LED included. IP rating: IP43 (ceiling mount), IP44 (wall mount). Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 350, H 130 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1550lm System power: 14W Beam Angle: 119° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 20,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14 W	CRI	80
Total flux	1550 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	11%
		Total power	14 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.12 in

Diameter: 13.78 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 43

IK: 10