

Product data sheet


AVENUE METRO RECESSED
 OPAL_1500MM_WHITE
 WHITECROFT



IP
20


1m - Modular linear LED system with a modern minimalist aesthetic for continuous or stand alone applications. Opal optics. Create long lines and angles of light with a seamless aesthetic – as Whitecroft Lighting AVENUE METRO. Emergency Lithium Output: 349lm

Light output 1 (emergency)



1 x LED


| | | | |
|--------------------|----------|-------------|--------|
| Nominal lamp power | 1 W | LOR | 100% |
| Lamp flux | 339 lm | Total flux | 339 lm |
| Luminous efficacy | 339 lm/W | Total power | 1 W |
| CCT | 3000 K | | |
| CRI | 80 | | |



1 x LED


| | | | |
|--------------------|----------|-------------|--------|
| Nominal lamp power | 1 W | LOR | 100% |
| Lamp flux | 359 lm | Total flux | 359 lm |
| Luminous efficacy | 359 lm/W | Total power | 1 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

Light output 2




1 x LED


| | | | |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 40 W | LOR | 100% |
| Lamp flux | 4089 lm | Total flux | 4089 lm |
| Luminous efficacy | 102 lm/W | Total power | 40 W |
| CCT | 3000 K | | |
| CRI | 80 | | |



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 40 W | LOR | 100% |
| Lamp flux | 4254 lm | Total flux | 4254 lm |
| Luminous efficacy | 106 lm/W | Total power | 40 W |
| CCT | 4000 K | | |
| CRI | 80 | | |



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 15 W | LOR | 100% |
| Lamp flux | 1788 lm | Total flux | 1788 lm |
| Luminous efficacy | 115 lm/W | Total power | 15.5 W |
| CCT | 3000 K | | |
| CRI | 80 | | |



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 15 W | LOR | 100% |
| Lamp flux | 1865 lm | Total flux | 1865 lm |
| Luminous efficacy | 120 lm/W | Total power | 15.5 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.15 in

Width: 59.06 in

Height: 3.27 in

Adjustability

Fixed

Electric

System power: 16.5-41 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

Protection

IP: 20