Product data sheet

SLIMBLEND RECTANGULAR, RECESSED RC400B POE W30L120 EL3 EM 1 XLED42S/840 RC402B


PHILIPS





SlimBlend Rectangular - High performance, advanced control Office norm-compliant lighting with good quality of light is in demand. Moreover, there is also an increasing need for comfort-enhancing effects such as diffused lighting and lighting smoothly blending into the ceiling architecture. That's why 'surface of light' solutions are becoming more and more popular. But parallel to these needs, are the demands to reduce energy and maintenance costs. SlimBlend answers all these needs and more. Not only does it provide glare-free comfort with a diffuse effect and clutter-free aesthetics thanks to integrated control options, it also creates a special blending of light. It uses the 'trapped' light under the masking to create a subtle glow, with a soft transition to the edge, lowering the brightness perception and blending the light into the ceiling. SlimBlend can also be part of a connected lighting system and integrated into the IT infrastructure enabling data on usage to be collected to help reduce energy costs and enhance employee comfort further. Also, thanks to the slim design, it enables technical equipment to be more easily installed in the plenum. Moreover, thanks to the variety of ways of mounting, various ceiling types can take advantage of this luminaire family. SlimBlend comes in square, rectangular and can be either recessed, surface-mounted, suspended. It offers a good balance between initial cost and ROI, making it the ideal choice for delivering excellent quality of light and a fast Return on Investment for offices.

Light output 1



1 x LED	
Nominal lamp power	3 W
Lamp flux	410 lm
Luminous efficacy	137 lm/W
CCT	4000 K
CRI	80

LOR 100%
Total flux 410 lm
Total power 3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.13 in Width: 11.69 in Height: 1.97 in Electric

System power: 3 W