



Product data sheet

LED PANEL FRAME 600, 40W, WARM WHITE, PUSH/DALI DIMMABLE
115178
ISOLED



DECO LINE FRAME 600 Series LED Panel, 40W, Warm White, Dimmable via Push or DALI, Aluminum Frame, IP42 Rated | Dimensioned power: 40 W | Effective power: 38 W | Energy efficiency class: E (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Material: aluminum | Surface color: White | Protection rating: IP42 | Suitable for indoor use only | Allowable ambient Temperatures: -20° - 40° C | Beam angle: 120° fixed | Color temperature: 3000K | Color rendering index: 83 (Ra 1-8) | Luminous flux: 3600 lm | DALI or push dimmable | Incl. external replaceable transformer | Usable service life: 71000 h (L80|B50) | Warranty: 3 years | FABRICATION: ISOLED 115178

Light output 1



1 x LED

Nominal lamp power	38 W	LOR	100%
Lamp flux	3600 lm	Total flux	3600 lm
Luminous efficacy	95 lm/W	Total power	38 W
CCT	3000 K		
CRI	83		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.43 in

Width: 23.43 in

Height: 0.43 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: White

Electric

System power: 38 W

Ballast: ECG

Controller: DALI

Protection

IP: 42

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F