


Product data sheet

BOLLARDS - TAURO 4000K
ATAURO/1/BK (6W 4000K)
ANSELL LIGHTING



• Robust die-cast aluminium bollard with a textured graphite finish suitable for education, commercial and hospitality outdoor applications • CCT selectable between 3000K and 4000K and power selectable; offering a choice of outputs, in one luminaire • Half-shield lens option to offer single direction output • High efficiency of 104lm/w • Precision-engineered lensed optic delivers exceptional light distribution and performance, ensuring maximum efficiency and visual comfort • Corrosion resistance up to C4M • Removable head design allows easy access to the integrated CCT and wattage switches, seamlessly housed within the head for quick adjustments and enhanced convenience during installation or maintenance • PIR option comes with integrated Photocell that can be switched as required • Comes complete with a AFIX connector (AFIXIP/1/SC/3C) for quick and easy IP rated connection • Supplied c/w base plate, root mounting kit accessory available

Light output 1



1 x LED			
Nominal lamp power	6.3 W	LOR	100%
Lamp flux	780 lm	Total flux	780 lm
Luminous efficacy	124 lm/W	Total power	6.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard, Pole top mounted

Electric

System power: 6.3 W

Shape and measurements

Length: 7.95 in
Width: 7.95 in
Height: 39.33 in

Protection

Designation labels: CE

Adjustability

Fixed