Product data sheet

BALEVA
451215.002.1
RZB



IP 00 IK 07

Series: Baleva Type of Protection: IP 40, IP 44 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Base and end caps made of white plastic. Diffuser in opal plastic. Converter integrated and encapsulated. Lamp (LED) included. IP40 ceiling installation, IP44 wall installation. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 500, B 46, H 60 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Impact Protection: IK07 (2 Joule) Luminaire flux LED: 900lm System power: 10W Beam Angle: 149°/107° Number of fittings B10A: 15 Number of fittings B16A: 25 Number of fittings C10A: 31 Number of fittings C16A: 50 Inrush current: 3,2A Unified Glare Ratio: 24,1 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	1000 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	18%
		Total power	10 W

Mounting mode

Wall mounted

Shape and measurements

Length: 1.77 in
Width: 19.69 in
Height: 2.36 in

Adjustability

Fixed

Electric

System power: 10 W

Protection

IP: 00
IK: 07