

# Product data sheet

PRO-VISION MINI, 36LEDS OPTIEK 6


41343X5X

PROLUMIA




Light Source: Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium FP programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

## Light output 1




1 x LED

Nominal lamp power	43.9 W	LOR	100%
Lamp flux	5800 lm	Total flux	5800 lm
Luminous efficacy	132 lm/W	Total power	43.9 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	46.4 W	LOR	100%
Lamp flux	5800 lm	Total flux	5800 lm
Luminous efficacy	125 lm/W	Total power	46.4 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	39.4 W	LOR	100%
Lamp flux	5200 lm	Total flux	5200 lm
Luminous efficacy	132 lm/W	Total power	39.4 W
CCT	4000 K		
CRI	80		




**1 x LED**

Nominal lamp power	41.6 W	LOR	100%
Lamp flux	5200 lm	Total flux	5200 lm
Luminous efficacy	125 lm/W	Total power	41.6 W
CCT	3000 K		
CRI	80		




**1 x LED**

Nominal lamp power	34.8 W	LOR	100%
Lamp flux	4600 lm	Total flux	4600 lm
Luminous efficacy	132 lm/W	Total power	34.8 W
CCT	4000 K		
CRI	80		




**1 x LED**

Nominal lamp power	36.8 W	LOR	100%
Lamp flux	4600 lm	Total flux	4600 lm
Luminous efficacy	125 lm/W	Total power	36.8 W
CCT	3000 K		
CRI	80		



**1 x LED**

Nominal lamp power	30.3 W	LOR	100%
Lamp flux	4000 lm	Total flux	4000 lm
Luminous efficacy	132 lm/W	Total power	30.3 W
CCT	4000 K		
CRI	80		



**1 x LED**

Nominal lamp power	32 W	LOR	100%
Lamp flux	4000 lm	Total flux	4000 lm
Luminous efficacy	125 lm/W	Total power	32 W
CCT	3000 K		
CRI	80		

**Mounting mode**

Ceiling mounted, Pole top mounted

**Shape and measurements**

Length: 23.62 in

Width: 12.40 in

Height: 5.31 in

**Electric**

System power: 30.3-46.4 W

Appliance Class: 0

## Protection

IP: 66

IK: 08

Designation labels: CE