



Product data sheet

ALVA BL 940/170 OP 360° 800 830 AN
EL10820045
ESYLUX



LED bollard made from high-grade aluminium Control system: ON/OFF Installation type: Free standing Installation position: Floor Dimensions: Height/Depth 940 mm, Ø 170 mm Weight: 7720 g Protection type: IP65 ApplianceClass: Class I Permissible ambient temperature: -25 °C...+40 °C Colour: graphite grey, similar to RAL 7024 Nominal voltage: 110 - 240 V AC / 50 - 60 Hz TotalSystemPower: 16 W Luminous flux: 1030 lm Luminous efficacy: 64 lm/W Colour temperature: 3100 K Colour rendering index R_a: > 80 Rated lifetime L₈₀>50</sub> at 25 °C: 70000 h<p>ArticleNumber: EL10820045 <https://www.esylux.com/p/EL10820045>

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1030 lm	Total flux	1030 lm
Luminous efficacy	64 lm/W	Total power	16 W
CCT	3100 K		
CRI	81		

Mounting mode

Standing / Bollard

Shape and measurements

Height: 37.01 in
Diameter: 6.69 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite

Electric

System power: 16 W
Ballast: ECG
Appliance Class: I

Protection

IP: 65
IK: 10
Designation labels: CE

Other operating numbers

Ambient temperature range: -13...104°F