Product data sheet


ARK MINI III 3000K 30W ANTHRACITE
7748448
WESTAL



IP 44 IK 10


Luminaire with dimmed downward-facing light emission. Chromated and powder-coated frame, anti-glare in PET-G. Equipped with replaceable LED unit. With cable relief and quick-connect terminal block 3x2x2.5 mm². Suitable for use in both private and public environments. Dimmable with leading-edge and trailing-edge control. The luminaire can be ordered in any color.

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	625 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	10 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	625 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	10 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	625 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	10 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 22.05 in
Width: 23.78 in
Height: 10.04 in

Adjustability

Fixed

Electric

System power: 30 W
Appliance Class: I

Protection

IP: 44
IK: 10