

# Product data sheet

TRL2 L180  
TRACER LED2  
DEXTRA




IP  
20



Tracer LED Lowbay 2 - 2 Card, IP20 Lowbay luminaire, slimline steel powder painted white body, polycarbonate cover, internal LED cover for optical control with hinged control gear covers for ease of access and wiring. Options: E3 - Emergency control gear (608 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) RD - Reacta-Dim Wireless Module TRL 5M SUSPENSION - Tracer LED suspension kit DS - Double switched

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	113.3 W	CRI	80
Total flux	13982 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	113.3 W

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 20.67 in  
Width: 19.88 in  
Height: 2.76 in

## Adjustability

Fixed

## Electric

System power: 113.3 W  
Ballast: ECG

## Protection

IP: 20  
Designation labels: CE