


Product data sheet

DEECOS R MINI
911471.002.1
RZB



Series: Deecos Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Horizontal rotation range: 356°, vertical swivel range: 90°. Can be swivelled flush with the ceiling. Installation without tool thanks to spring fastening system. Heat resistant plastic ring. Reflector material: MIRO-SILVER with 98% total light reflection, can be changed without tools. Lamp (LED) included. Converter in separate converter housing. With connected connecting cable between luminaire and converter housing Available Colours: Traffic white, matt (RAL 9016) Type of Installation: Recessed ceiling mounting Dimensions: D 143, H 3 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 3200lm System power: 29W Beam Angle: 32° Number of fittings B10A: 21 Number of fittings B16A: 34 Number of fittings C10A: 35 Number of fittings C16A: 57 Inrush current: 18,6A Unified Glare Ratio: 16,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	30 W	CRI	80
Total flux	3100 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	30 W

Mounting mode

Wall mounted

Shape and measurements

Height: 8.43 in
Diameter: 5.63 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: White

Electric

System power: 30 W

Protection

IP: 20
IK: 06