Product data sheet


DISC 480 BLACK D/I 4000LM 3000K RA>80 SENSOR DIM
7021986062090
SG ARMATUREN



IP 20 IK 10

Disc 480 D/I is an energy efficient and stylish surface-mounted luminaire with a slim profile, providing any room with a modern and refined look. Opal prismatic diffuser ensures glare-free and comfortable lighting with a decorative indirect light. It is possible to choose between 3000K/4000K with the connection cable. Disc 480 D/I is produced in durable aluminium and polycarbonate. Installation is simple, thanks to the quick connection between the luminaire and the backplate, which can be mounted directly onto all standard ceiling boxes. Visible cabling also possible. Light distribution Direct/Indirect Light technic LED 34W 3000K Ra>80 SDCM 3 L80/B20 >100,000 hrs L90 >50,000 hrs Control/Dimming Sensor Dim Protection Class II IP20 IK10 Materials and finish Housing: Aluminium/Plastic Colour: Black Optics: Acrylic (PMMA) Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light output 1



1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4000 lm	Total flux	4001 lm
Luminous efficacy	118 lm/W	Total power	34 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 18.52 in
Width: 18.52 in
Height: 2.44 in

Adjustability

Fixed

Electric

System power: 34 W
Appliance Class: II

Protection

IP: 20
IK: 10