


# Product data sheet

1M RT 2-5000 24V RGBW-ONE DAY 2X (5060, 300 LED, LUX)  
019151  
ARLIGHT RUS LLC




Гибкая лента LUX, светодиоды smd 5060 RGBW 4-в-1, 60шт/м Цвет RGB + Дневной 3800-4200K. Питание 24V, мощность 4.8 Вт/м на канал R/G/B/W, общая 19.2 Вт/м Угол 120°, цветопередача CRI>85. Размеры 5000x12x2.2мм. Мин.отрезок 100мм, 6шт светодиодов. Рекомендуется установка на профиль.


## Light output 1




|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 3.7 W   | LOR         | 100%   |
| Lamp flux          | 340 lm  | Total flux  | 340 lm |
| Luminous efficacy  | 92 lm/W | Total power | 3.7 W  |
| CCT                | 4087 K  |             |        |
| CRI                | 84      |             |        |



|                    |         |             |       |
|--------------------|---------|-------------|-------|
| 1 x LED            |         |             |       |
| Nominal lamp power | 3.9 W   | LOR         | 100%  |
| Lamp flux          | 99 lm   | Total flux  | 99 lm |
| Luminous efficacy  | 25 lm/W | Total power | 3.9 W |
| CCT                | 0 K     |             |       |
| CRI                | -29     |             |       |



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 4.3 W   | LOR         | 100%   |
| Lamp flux          | 247 lm  | Total flux  | 247 lm |
| Luminous efficacy  | 57 lm/W | Total power | 4.3 W  |
| CCT                | 0 K     |             |        |
| CRI                | -18     |             |        |



|                    |         |             |       |
|--------------------|---------|-------------|-------|
| 1 x LED            |         |             |       |
| Nominal lamp power | 4 W     | LOR         | 100%  |
| Lamp flux          | 73 lm   | Total flux  | 73 lm |
| Luminous efficacy  | 13 lm/W | Total power | 4 W   |
| CCT                | 0 K     |             |       |
| CRI                | -50     |             |       |

**Mounting mode**

Ceiling mounted

**Electric**

System power: 3.7-4.3 W

**Shape and measurements**

Length: 39.37 in

Width: 0.47 in

Height: 0.12 in

**Protection**

IP: 33

**Adjustability**

Fixed