

Product data sheet

CEILING MOUNTED LUMINAIRE PUREFACE OFFICE 30W 3600LM CRI > 90 3000K WHITE DALI2 925MM


2011.3306 - PURFC O CM925X150 LED3600-930 DALI

REGENT



Ceiling mounted luminaire Pureface Office with LED, system power: 30 W, standby power 0.5 W, luminous flux of luminaire 3600 lm, colour rendering index CRI > 90, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L90B10>100000 h, office-compatible and glare-free according to EN 12464-1 ($UGR < 19$; $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$), photobiological safety: the luminaire poses no danger (RG0), 230 V, omni-directional, incl. illumination of the ceiling, housing in aluminium, white RAL 9016, diffuser in synthetic material RUN+, office-suitable, for a perfectly glare-free light line, 1 integral control gear, DALI2, Extra-flat construction of only 35 mm incl. control gear, diffuser and optics in one piece without interruptions, optics evenly and softly illuminated without visible LED points, front side illuminated, without visible screws, use of an IP54 luminaire in a clean environment (office) enables an increase in the maintenance factor in accordance with CIE 97:2005 or an extension of the maintenance interval. LED boards Can be replaced on site during maintenance protection class I, ingress protection IP54, glow wire test 650 °C, impact strength: IK 04, this product contains a light source of energy efficiency class C L = 925 mm, B = 150 mm, H = 35 mm

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	90
Total flux	3600 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	30 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 0.04 in

Width: 0.04 in

Height: 0.04 in

Weight: 0.846 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 30 W

Appliance Class: I

Protection

IP: 54

IK: 04