

# Product data sheet

MIXS67-600 LED 2500 840  
GLAMOX




IP  
67

IK  
10

Light source LED Ballast Electronic ballast (HF). Body material & colour Housing in Aluzink or acid-proof steel with white epoxy/polyester powder coated finish. Alternatively in unpainted acid-proof steel. The diffuser is made of impact-proof polycarbonate (PC) with moulded silicone gasket and spring clips in acid-proof steel. Mounting The luminaire is supplied with fixed end brackets, triangle suspension or 2 x M8 hood nuts. Bracket for horizontal wire and revolable bracket to be mounted on the fixed end bracket. M8 rod -, tube -, pole -, cable bridge -, side - and vibration suspension to be mounted through the M8 hood nut. M8 hood nuts with flexible CC and other special suspensions on request. Accessories Suspension kits. Connection 5 pole 6 mm² screw terminal block. Variants with 5 x 2,5 mm² through wiring.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2565 lm	LOR	100%
Luminous efficacy	135 lm/W	ULOR	5%
		Total power	19 W

## Mounting mode

Ceiling mounted

## Electric

System power: 19 W

## Shape and measurements

Length: 28.50 in  
Width: 6.50 in  
Height: 5.04 in

## Protection

IP: 67  
IK: 10

## Adjustability

Fixed