
Product data sheet

ACTOR G2 PENDANT MP VIT CASAMBI PIR 30 70 3000K*
7028476
HIDE-A-LITE



Actor G2 Pendant is a suspended interior luminaire designed for easy installation and high visual comfort. Available in white or black powder-coated aluminium, it suits any modern environment. The suspension kit allows you to adjust the height effortlessly, and the built-in DIP switch lets you set both light distribution and colour temperature directly on site—quickly, precisely and without tools. No need to decide everything in advance; the light can be adjusted once the installation is complete. The design is modular, meaning you only replace the needed part—not the entire luminaire. It can be installed as a single unit or linked into long light lines. Choose between up/down light distribution of 30/70 or 50/50, depending on whether you want more work light downwards or ambient light upwards. Select between opal, microprismatic or double parabolic glare shields. The double parabolic version meets screen and UGR requirements (UGR < 19 for offices) under standard conditions. Delivered complete with ceiling mounting accessories, earthed cable set or 5-pole DALI cable with open ends.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	41 W	CRI	90
Total flux	5757 lm	LOR	100%
Luminous efficacy	140 lm/W	ULOR	8%
		Total power	41 W

Mounting mode

Pendant

Shape and measurements

Length: 47.48 in
Width: 2.05 in
Height: 3.07 in

Adjustability

Height adjustable

Design

Designer: Elektro Elco AB

Electric

System power: 41 W
Color adjustable
Appliance Class: I

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 20
Designation labels: CE