

# Product data sheet


T8防水防尘支架  
PAK319610 PAK-A07-218  
PAK




IP  
65

灯体采用高强度聚碳酸酯透明PC材料，具有抗撞击耐紫外线，寿命更长，阻燃性好。配合T8 直管荧光灯使用，适用于地下室、工厂、学校及户外建筑轮廓照明及各种有防水防尘要求场所。

## Light output 1



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 2 x LED            |         |             |        |
| Nominal lamp power | 9 W     | Socket      | 2G13   |
| Lamp flux          | 700 lm  | LOR         | 71%    |
| Luminous efficacy  | 28 lm/W | ULOR        | 13%    |
| CCT                | 4000 K  | Total flux  | 995 lm |
| CRI                | 85      | Total power | 36 W   |



|                     |         |             |         |
|---------------------|---------|-------------|---------|
| 2 x 18W/T8真亮彩荧光灯管 - |         |             |         |
| Nominal lamp power  | 18 W    | Socket      | G13     |
| Lamp flux           | 1250 lm | LOR         | 71%     |
| Luminous efficacy   | 49 lm/W | ULOR        | 13%     |
| CCT                 | 6500 K  | Total flux  | 1776 lm |
| CRI                 | 85      | Total power | 36 W    |

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 6.30 in  
Width: 26.38 in  
Height: 4.33 in

## Adjustability

Fixed

## Electric

System power: 36 W

## Protection

IP: 65