


Product data sheet

SIRI 3.0 L [3000K 23W 230VAC]
SR30105LT
L&L LUCE&LIGHT



Projector for outdoor applications; surface mounted (ceiling, wall, ground, stake); body in die-cast aluminium alloy EN AW 47100, screen in serigraphed, tempered glass; finishes: anthracite, white, cor-ten, grey; 9 power LEDs; 23W - 230Vac; built in power supply unit; includes 1,5 m neoprene cable, H05RN-F 3x1,0 Ø7 mm; total delivered lumens: 1491 lm (3000K); optics: 6°, 12°, 30°, 40°, 10°x45°; LED colour: white - 2700K, 3000K, 4000K, 5000K; ingress protection: IP66; impact resistance: IK06; IPS built into the cable gland; operating temperature: -10°C +45°C; screen temperature: max 40°C (Ta 25°C); Glow wire test: 960°; photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: I; weight 2,10 kg; dimensions 283x170x48 mm; dimming with 0-10V; accessories: stake WP0300, honeycomb louvre WH5030, anthracite anti-glare hood WB5030H

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	23 W	CRI	80
Total flux	1248 lm	LOR	100%
Luminous efficacy	54 lm/W	Total power	23 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 1.61 in
Width: 7.04 in
Height: 5.53 in

Adjustability

Tiltable

Electric

System power: 23 W
Appliance Class: I

Protection

IP: 66
IK: 06