Product data sheet

GOLAS MAXI
911455.002.1
RZB



IP 20 IK 03

Series: Golas Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Horizontal rotation range: 356°, vertical swivel range: 65°. Installation without tools thanks to spring fastening system. Heat resistant plastic ring. Lens made of plastic (polycarbonate) included, can be changed without tools. Lamp (LED) included. Converter in separate converter housing. With connected connecting cable between luminaire and converter housing. Available Colours: Traffic white, matt (RAL 9016) Type of Installation: Recessed ceiling mounting Dimensions: D 178, H 3 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2500lm System power: 24W Beam Angle: 41° Number of fittings B10A: 21 Number of fittings B16A: 34 Number of fittings C10A: 35 Number of fittings C16A: 57 Inrush current: 18,6A Unified Glare Ratio: 13,1 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27 W	CRI	80
Total flux	2500 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	27 W

Mounting mode

Wall mounted

Shape and measurements

Height: 0.12 in
Diameter: 7.01 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: White

Electric

System power: 27 W

Protection

IP: 20
IK: 03