


Product data sheet

S36H-PD237 DAFWS830DPS0400
SPG0630288AH
RIDI



Pendant luminaire S36H Design: Modern direct distribution pendant luminaire. Luminaire made from aluminium profile, white (...FWS...), silver (...SI...) or black (...FSW...),fine-grained. Suspension of luminaire via Y-shaped steel wire, max. 1.5 m in length, smooth height adjustment. Transparentconnecting cable, 1.5 m in length. Luminaire fitted with RIDI LED modules. LED module for direct component mounted at the bottom in the aluminium profile. Direct component covered by a transparent extruded plastic cover, in clear UV stabilised PMMA with external diamond-shaped microprism structure to reduce glare. LEDs visible as dots. All electrical components are integrated into the luminaire. Colour rendering in index at least Ra 80, light colour 830 (3000 Kelvin), 840 (4000 Kelvin) or TW (TunableWhite, 3000–6500 Kelvin). Protection rating IP20, protection class I.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	45 W	CRI	80
Total flux	3930 lm	LOR	77%
Luminous efficacy	87 lm/W	Total power	45 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 93.50 in
Width: 1.42 in
Height: 2.76 in

Adjustability

Fixed

Electric

System power: 45 W
Appliance Class: I

Protection

IP: 20