Product data sheet

LTUB60 SUT 840 1500 VWW D/I OPAL WE
L61ST084LOIO927N3
LAMP



IP 20 IK 07

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Light output 1



1 x LED

Nominal lamp power	9.7 W	LOR	100%
Lamp flux	698 lm	Total flux	698 lm
Luminous efficacy	72 lm/W	Total power	9.7 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 34.02 in
Width: 2.76 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Black, White

Electric

System power: 9.7 W
Appliance Class: I

Protection

IP: 20
IK: 07