Product data sheet

P.THIRTY SUSP. L-SEG.HOR. WHITE DI/ID PRISM.
P30-HLFH9016C2840H3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 20

LED HO 4000K 24,8W 4111lm¹ DALI CRI90 ¹ Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 6,9% https://katalog.planlicht.com/en-gb/search?q=p.thirty&type=1-profile-segment

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 9 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Light output 10 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	90
Total flux	411 lm	LOR	100%
Luminous efficacy	166 lm/W	Total power	2.48 W

Mounting mode

Pendant

Shape and measurements

Length: 11.57 in

Width: 25.31 in

Height: 1.38 in

Adjustability

Fixed

Electric

System power: 24.8 W

Protection

IP: 20

Designation labels: CE